








Installation Instructions

CPT-12U Cable Prep Tool for LDF4 / AL4RPV / HL4RP Style Cables

Andrew Institute offers installation training.

 <p>Part number: CPT-12U Blade Kit number: CPT-BK12U</p> <p>Part number: CPT-ICT12U</p>	<p>1</p>  <p>Ensure the last 12"(305mm) of cable is straight and cut square before using the tool. The cordless drill is recommended (3/8" 14.4V minimum / 1/2" 18V recommended). Operate the drill in the 1500-1800 rpm range. We recommend two or more "test runs" to become familiar with the spring-loaded locating system that controls the cable preparation dimensions. Use scrap cable in vise.</p>
<p> When this tool is used in a powered drill, the user is advised to wear suitable eye protection and gloves. Your Safety Program should include but should not be limited to standards of OSHA, NEC and NESC.</p>	
<p>2</p>  <p>Operating drill speed 1500-1800 rpm range</p> <p>Insert the tool on the cable and operate the drill in a fluid clockwise direction with slight forward pressure. As the spring-loaded ball bearings pass over the crest of the corrugation you will feel resistance from the springs and from the blades as they cut the cable. When the ball bearings fall into the corrugation valley you will hear the pitch of the drill motor increase and the resistance subside. The blades have finished their cut. Allow the drill to turn a few extra revolutions without applying any forward pressure. This will ensure a clean and uniform preparation.</p>	<p>3</p>  <p>Stop the drill and remove from cable.</p> <p>Note: If operating the drill during removal from the cable, first reverse the motor. This prevents the jacket cutting blade from contacting the now exposed outer conductor during drill removal.</p>
<p>4</p>  <p>Remove insulation that extends beyond the outer conductor, making sure insulation is flush with edge of outer conductor.</p> <p>Note: When removing insulation, ensure inner conductor is not scratched or damaged.</p>	<p>5</p>  <p>Use compression tool by inserting on inner conductor and turning clockwise to compress the outer edge of insulation.</p> <p>Refer to bulletin 237903 to complete installation.</p>

Andrew LLC
Customer Service 24 hours
U.S.A., Canada, Mexico:
for HELIAX® AVA Cables call 1-800-255-1479
for HELIAX® SFX, FXL Cables call 1-888-235-5732
U.K.: 0800 250055
Other Europe: +44 592 782 612

www.commscope.com
Visit our Web site at www.commscope.com or contact your local Andrew LLC representative for more information.
© 2009 CommScope, Inc. All rights reserved.
Andrew LLC is a trademark of CommScope. All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to Andrew LLC products or services.

Notice: Andrew LLC disclaims any liability or responsibility for the results of improper or unsafe installation, inspection, maintenance, or removal practices.
Aviso: Andrews LLC no acepta ninguna obligación ni responsabilidad como resultado de prácticas incorrectas o peligrosas de instalación, inspección, mantenimiento o retiro.
Avis : Andrew LLC décline toute responsabilité pour les conséquences de procédures d'installation, d'inspection, d'entretien ou de retrait incorrectes ou dangereuses.
Hinweis: Andrew LLC lehnt jede Haftung oder Verantwortung für Schäden ab, die aufgrund unsachgemäßer Installation, Überprüfung, Wartung oder Demontage auftreten.
Atenção: A Andrew LLC abdica do direito de toda responsabilidade pelos resultados de práticas inadequadas e sem segurança de instalação, inspeção, manutenção ou remoção.
Avvertenza: Andrew LLC declina eventuali responsabilità derivanti dall'esecuzione di procedure di installazione, ispezione, manutenzione e smontaggio improprie o poco sicure.
注意: Andrew 公司申明對於不恰當或不安全的安裝、檢驗、維修或拆卸操作所導致的後果不負責任何義務和責任

