

T-10-UW-43-M

Termination Load, 0–6000 MHz, Not for PIM-rated applications



Product Classification

| | |
|------------------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Product Type | Termination Load |

General Specifications

| | |
|------------------------------|------------------|
| Device Type | Termination Load |
| Application | Indoor/Outdoor |
| Color | Black |
| Inner Contact Plating | Silver |
| Interface | 4.3-10 Male |
| Outer Contact Plating | Trimetal |

Dimensions

| | |
|--------------------------|------------------|
| Length | 53 mm 2.087 in |
| Diameter, maximum | 35 mm 1.378 in |

Electrical Specifications

| | |
|---------------------------------|--------------|
| Average Power, maximum | 10 W |
| Impedance | 50 ohm |
| Operating Frequency Band | 0 – 6000 MHz |
| VSWR | 1.15 |

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Operating Temperature | -35 °C to +50 °C (-31 °F to +122 °F) |
| Relative Humidity | Up to 100% |

T-10-UW-43-M

Ingress Protection Test Method IEC 60529:2001, IP65

Packaging and Weights

Height, packed 53 mm | 2.087 in

Width, packed 58 mm | 2.283 in

Length, packed 68 mm | 2.677 in

Weight, gross 0.16 kg | 0.353 lb

Weight, net 0.13 kg | 0.287 lb

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |

